product details **80193**

Product description:	80193
Product code:	4008321376596
Quantity:	Blister (BLI) contains 1 Piece (PCE)

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321376596

Applications	
Dimmable	No
With on/off switch	Yes
Accessories	Magnet | Screw | 3 x 1.5 V MICRO LR3 AAA
Adjustable	Yes
Type of sensor	Day/Night
Type of connection	NOT RELEVANT
Type of cover	CLEAR

Certificates & Standards	
Protection class	III
Type of protection	IP54
Standards	CE

General Description	
Number of lighting outlets	3
Equipment	LED
Recycling	Yes
Equipped with lamp	Yes
Body material	PLASTICS
Reflector material	VAPOURISED PLASTIC

Technical - Colors	
Product color	WHITE

Technical - Electrical Data	
Nominal wattage	0.3 W
Nominal voltage	4.5 V
Mains frequency	0 Hz
Nominal current	60.0 mA

Technical - Geometries	
Diameter	88 mm
Length	86.00 mm
Width	69.00 mm
Height	28.00 mm

Technical - Light Technical Data	
Beam angle	120 °

Technical - Temperatures	
Ambient temperature range	...+25 °C

Subject to change without notice. Errors and omission excepted.
© 2011 OSRAM GmbH

product details 80193

Packaging units				
Product code	**Packaging type and content**	**Dimensions in h x w x l**	**Gross weight**	**Volume**
4008321376596	Blister contains 1 Piece	117,000 mm x 35,000 mm x 185,000 mm	132,000 g (0,000 g)	0,881 Cubic dec.
4008321376602	Shipping carton box contains 6 Piece	178,000 mm x 143,000 mm x 195,000 mm	873,000 g (0,000 g)	21,431 Cubic dec.

NIGHTLUX

NIGHTLUX - the easy-to-install night light without cables or plugs, provides light in dark corners and on steep staircases. The design of NIGHTLUX makes it ideal particularly for illuminating the lower third of a room. When mounted at hip height its three LED lamps illuminate everyday obstacles and therefore cut down the risk of accidents. After 10 or 60 seconds it automatically switches off again.

- Dustproof and splashproof, suitable for indoor and outdoor applications
- Easy to install with screws, magnets or adhesive strip
- The LED luminaire can be swiveled up and down through an angle of 60 degrees
- CE Sign Protection class III, IP54, 4.5 V

Subject to change without notice. Errors and omission excepted.
© 2011 OSRAM GmbH